

## Pipe Laying Hook



- *Carrying capacities up to 7,5 t*
- *Equipped with an automatic weight counterbalance*
- *For pipe lengths up to 3 m*
- *Equipped with a safety chain as standard*

**Model RHK -  
for pipe lengths up to 1 m**



Order No.	Model	Carrying capacity kg	Throat width mm	Weight approx. kg
115 010	RHK 1/1	1000	190	24
115 025	RHK 3/1	3000	260	45

**Model RHSV -  
for pipe lengths up to 3 m, equipped with an automatic  
weight counterbalance and adjustable limit stop**



Order No.	Model	Carrying capacity kg	Throat width mm	Min. Weight* approx. kg	Weight approx. kg
115 210	RHSV 1/3	1000	300	350	180
115 325	RHSV 3/3	3000	460	1000	310
115 335	RHSV 7,5/3	7500	500	3000	732

\* For the functioning of the automatic system a minimum pipe weight for each RHSV pipe laying hook is necessary. Pipes with smaller weights cannot be handled with this equipment.

# 120

## Pipe Chain Sling With Hooks

*The pipe chain sling with hooks is designed for easy and convenient loading and unloading of all types of pipes. It consists of two pipe hooks and a two-leg chain sling, whose lengths are designed to handle pipes up to 4 m.*



*All pipe chain slings with hooks are delivered with a 2-leg chain sling and a device for shortening and lengthening the chain sling for pipe lengths up to 4 m.*

Order No.	Model for pipes of 4 m	Carrying capacity kg	Throat width approx. mm	Weight approx. kg
120 010	ROG 1/4	1000	200	31
120 020	ROG 2.5/4	2500	250	56
120 030	ROG 4/4	4000	320	101

For an additional charge rubber-lined throat width is available. In this way the throat width is reduced by 50 mm.