

Aluminium Tripod



Order No.	Model	Carrying Capacity	Length Of Support L Min./Max.	Clearance Height ¹⁾ H Min./Max.	Spreading Angle ¹⁾ B Min./Max.	Weight Approx.
140 001	D-250	250 kg	1,18 / 1,88 m	0,94 / 1,58 m	0,95 / 1,50 m	10 kg
140 009 F	D-250 Mobile	250 kg	1,85 / 3,10 m	1,46 / 2,57 m	1,40 / 2,40 m	36 kg
140 003	D-500	500 kg	1,50 / 2,50 m	1,15 / 2,05 m	1,20 / 1,95 m	17 kg
140 033	D-500/EN795 ²⁾	500 kg	1,50 / 2,50 m	1,15 / 2,05 m	1,20 / 1,95 m	17 kg
140 009	D-503	500 kg	1,76 / 3,00 m	1,45 / 2,63 m	1,43 / 2,39 m	20 kg
140 008	D-1000	1.000 kg	1,78 / 3,00 m	1,38 / 2,54 m	1,65 / 2,35 m	27 kg
140 014	D-1004	1.000 kg	2,25 / 4,00 m	1,86 / 3,44 m	1,79 / 3,07 m	36 kg

¹⁾ Max. spreading angle (25°)

²⁾ Permitted for man riding applications up to 150 kg according to EN 795. Equipped with rubber plates and safety chain. Suitable man riding rope lifting and lowering equipment available.

- Light aluminium construction
- Simple transport due to telescopic height adjustment
- Spikes as standard
- Equipped with swivelling suspension eye

Accessories:

- Rubber plates (for solid ground)
- Safety chain (for smooth ground)
- Hoist